



LEVELER – 6th HIGH TYPE

17 ROLLS Ø52 mm

REVAMPED



GENERAL FEATURES

• Max tensile strength	R _{max} =	680 N/mm ²
• Max yield strength	R _{max} =	400 N/mm ²
• Min thickness	mm	0,8
• Max thickness	mm	3,0
• Max coil width	mm	1550
• Variable working speed	m/min	50

LEVELER – 6th HIGH TYPE – n.17 ROLLS Ø52 mm

The leveler is equipped as follows:

- n. 17 working rolls, of which n. 9 lower rolls and n. 8 upper rolls;
- All leveling rolls have a diameter of 52 mm and a width of 1650 mm;
- The rolls are chromed;
- It is equipped with n.7 series of upper back-up rolls and n.7 series of lower back-up rolls;
- The motors are NOT included in the supply;
- Complete equipment on machine-board;
- Electric and hydraulic equipment NOT included.

MACHINE COLOURS

- Made by two coats of nitro paint and one coat of rustproof deep like preparation.
- moving parts : YELLOW RAL 1023
- all other parts : LIGHT BLUE RAL 5012



BEFORE



AFTER





GENERAL SALES CONDITIONS

1) PRICE

Leveler as per technical specification

TRANSPORTATION, PACKAGE AND INSURANCE - EXCLUDED

Transport, package and insurance are NOT included in this quotation – at Customer's charge.
Goods will be delivered EXW FASPAR.
Packing materials (special packaging only if requested by the Customer) will be invoiced at cost.

INSTALLATION AND COMMISSIONING – EXCLUDED

If required, it will be quoted separately.

2) PAYMENT TERMS

100% At the order date

3) DELIVERY

Prompt delivery for machine as-it-is and subject to prior sale.