



**LEVELER – 6<sup>th</sup> HIGH TYPE**

**21 ROLLS Ø39 mm**

**REVAMPED**



## **GENERAL FEATURES**

- |                          |                    |                       |
|--------------------------|--------------------|-----------------------|
| • Max tensile strength   | R <sub>max</sub> = | 680 N/mm <sup>2</sup> |
| • Max yield strength     | R <sub>max</sub> = | 400 N/mm <sup>2</sup> |
| • Min thickness          | mm                 | 0,4                   |
| • Max thickness          | mm                 | 1,5                   |
| • Max coil width         | mm                 | 1550                  |
| • Variable working speed | m/min              | 50                    |

### **LEVELER – 6<sup>th</sup> HIGH TYPE – 21 ROLLS Ø39 mm**

The leveler is equipped as follows:

- n. 21 working rolls, of which n. 11 lower rolls and n. 10 upper rolls;
- All leveling rolls have a diameter of 39 mm and a width of 1600 mm;
- The rolls are chromed;
- It is equipped with n.7 series of upper back-up rolls and n.7 series of lower back-up rolls;
- The motors are NOT included in the supply;
- Complete equipment on machine-board;
- Electric and hydraulic equipment NOT included.

## **MACHINE COLOURS**

- Made by two coats of nitro paint and one coat of rustproof deep like preparation.
- moving parts : YELLOW RAL 1023
- all other parts : LIGHT BLUE RAL 5012



**BEFORE**



**AFTER**





## **GENERAL SALES CONDITIONS**

### **1) PRICE**

*Leveler as per technical specification*

#### **TRANSPORTATION, PACKAGE AND INSURANCE - EXCLUDED**

Transport, package and insurance are NOT included in this quotation – at Customer's charge.  
Goods will be delivered EXW FASPAR.  
Packing materials (special packaging only if requested by the Customer) will be invoiced at cost.

#### **INSTALLATION AND COMMISSIONING – EXCLUDED**

If required, it will be quoted separately.

### **2) PAYMENT TERMS**

100% At the order date

### **3) DELIVERY**

Prompt delivery for machine as-it-is and subject to prior sale.